



 05		Marazzi Group s.r.l. a socio unico, Viale Regina Pacis 39 41049 Sassuolo (MO) 001MRZI https://www.marazzigroup.com/download/
For internal and/or external floorings, including stairs, in buildings and industrial facilities and for internal and/or external walls in buildings and industrial facilities	EN 14411:2012 Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5\%$, for internal and external walls and floorings	Breaking Strength: Thickness <7,5 mm Breaking Strength ≥ 700 N Thickness $\geq 7,5$ mm Breaking Strength ≥ 1300 N Reaction to fire: Class A1 _{FL} /A1 Thermal shock resistance: Pass Durability, for: - Internal uses: Pass - External uses- Freeze/thaw resistance: Pass


 05		Marazzi Group s.r.l. a socio unico, Viale Regina Pacis 39 41049 Sassuolo (MO) 002MRZI https://www.marazzigroup.com/download/
For internal and/or external floorings, including stairs, in buildings and industrial facilities and for internal and/or external walls in buildings and industrial facilities	EN 14411:2012 Dry-pressed ceramic tiles, with water absorption $0,5\% < E_b \leq 3\%$, for internal and external walls and floorings	Breaking Strength: Thickness <7,5 mm Breaking Strength ≥ 700 N Thickness $\geq 7,5$ mm Breaking Strength ≥ 1100 N Reaction to fire Class: A1 _{FL} /A1 Thermal shock resistance: Pass Durability, for: - Internal uses- Pass - External uses: Freeze/thaw resistance: Pass


For internal floorings, including stairs, in buildings and industrial facilities and for internal walls in buildings and industrial facilities		Marazzi Group s.r.l. a socio unico, Viale Regina Pacis 39 41049 Sassuolo (MO) 003MRZI https://www.marazzigroup.com/download/
 05	EN 14411:2012 Dry-pressed ceramic tiles, with water absorption $3\% < E_b \leq 6\%$, for internal walls and floorings	Durability, for - Internal uses: Pass Reaction to fire: Class A1 _{FL} /A1 Breaking Strength: Thickness <7,5 mm Breaking Strength ≥ 600 N Thickness $\geq 7,5$ mm Breaking Strength ≥ 1000 N


 05	<p align="center">Marazzi Group s.r.l. a socio unico, Viale Regina Pacis 39 41049 Sassuolo (MO) 004MRZI</p> <p align="center">https://www.marazzigroup.com/download/</p>	
Durability, for Internal uses: Pass Reaction to fire: Class A1	For internal walls in buildings and industrial facilities	EN 14411:2012 Dry-pressed ceramic tiles, with water absorption 6%<Eb≤10%, for internal walls


 05	<p align="center">Marazzi Group s.r.l. a socio unico, Viale Regina Pacis 39 41049 Sassuolo (MO) 005MRZI</p> <p align="center">https://www.marazzigroup.com/download/</p>	
Durability, for Internal uses: Pass Reaction to fire: Class A1	For internal walls in buildings and industrial facilities	EN 14411:2012 Dry-pressed ceramic tiles, with water absorption Eb> 10%, for internal walls


 05	<p align="center">Marazzi Group s.r.l. a socio unico, Viale Regina Pacis 39 41049 Sassuolo (MO) 006MRZI</p> <p align="center">https://www.marazzigroup.com/download/</p>	
Durability, for Internal uses: Pass Reaction to fire: Class A1	For internal walls in buildings and industrial facilities	EN 14411:2012 Dry-pressed ceramic tiles, with water absorption 3%<Eb≤6%, for internal walls

For internal floorings, including stairs, in buildings and industrial facilities and for internal walls in buildings and industrial facilities		<p align="center">Marazzi Group s.r.l. a socio unico, Viale Regina Pacis 39 41049 Sassuolo (MO) 007MRZI</p> <p align="center">https://www.marazzigroup.com/download/</p>
 05	EN 14411:2012 Dry-pressed ceramic tiles, with water absorption Eb>10%, for internal walls and floorings	Breaking Strength: Thickness <7,5 mm Breaking Strength ≥200 N Thickness ≥7,5 mm Breaking Strength ≥600 N Reaction to fire: Class A1 _{F1} /A1 Durability, for Internal uses: Pass

For internal floorings, including stairs, in buildings and industrial facilities and for internal walls in buildings and industrial facilities		<p>Marazzi Group s.r.l. a socio unico, Viale Regina Pacis 39 41049 Sassuolo (MO) 008MRZI</p> <p>https://www.marazzigroup.com/download/</p>
	<p>EN 14411:2012</p> <p>Extruded ceramic tiles, with water absorption Eb≤0,5%, for internal and external walls and floorings</p>	<p>Breaking Strength: Thickness <7,5 mm Breaking Strength ≥600 N Thickness ≥7,5 mm Breaking Strength ≥1300 N Reaction to fire: Class A1_F/A1 Thermal shock resistance: Pass Durability, for: - Internal uses: Pass - External uses: Freeze/thaw resistance: Pass</p>

	<p>Marazzi Group s.r.l. a socio unico, Viale Regina Pacis 39 41049 Sassuolo (MO) 009MRZI</p> <p>https://www.marazzigroup.com/download/</p>
<p>Thermal shock resistance: Pass Reaction to fire: Class A1 Durability, for: - Internal uses: Pass - External uses: Freeze/thaw resistance: Pass</p>	<p>For internal and/or external walls in buildings and industrial facilities</p> <p>EN 14411:2012 Dry-pressed ceramic tiles, with water absorption Eb≤0,5%, for internal and external walls</p>

	<p>Marazzi Group s.r.l. a socio unico, Viale Regina Pacis 39 41049 Sassuolo (MO) 010MRZI</p> <p>https://www.marazzigroup.com/download/</p>
<p>Thermal shock resistance: Pass Reaction to fire: Class A1 Durability, for: - Internal uses: Pass - External uses: Freeze/thaw resistance: Pass</p>	<p>For internal and/or external walls in buildings and industrial facilities</p> <p>EN 14411:2012 Dry-pressed ceramic tiles, with water absorption 0,5%<Eb ≤3%, for internal and external walls</p>

	<p>Marazzi Group s.r.l. a socio unico, Viale Regina Pacis 39 41049 Sassuolo (MO) 011MRZI</p> <p>https://www.marazzigroup.com/download/</p>
<p>Reaction to fire: Class A1 Durability, for: - Internal uses: Pass Thermal shock resistance: Pass</p>	<p>For internal walls in buildings and industrial facilities</p> <p>EN 14411:2012 Dry-pressed ceramic tiles, with water absorption Eb≤0,5%, for internal walls</p>