



**Marazzi Group s.r.l. a socio unico,  
Viale Regina Pacis 39  
41049 Sassuolo (MO)**

**05**

**001MRZI**

**EN 14411:2012**

**Dry-pressed ceramic tiles, with water absorption  $E_b \leq 0,5\%$ ,  
for internal and external walls and floorings**

Reaction to fire	Class A1 <sub>FL</sub> /A1
Breaking strength	Thickness <7,5 mm Breaking strength $\geq 700$ N Thickness $\geq 7,5$ mm Breaking strength $\geq 1300$ N
Slipperiness	See table attached
Durability, for: - Internal use - External use: Freeze/thaw resistance	Passed Passed
Resistance to thermal shock	Passed



**Marazzi Group s.r.l. a socio unico,  
Viale Regina Pacis 39  
41049 Sassuolo (MO)**

**05**

**002MRZI**

**EN 14411:2012**

**Dry-pressed ceramic tiles, with water absorption  $0,5\% < E_b \leq 3\%$ ,  
for internal and external walls and floorings**

Reaction to fire	Class A1 <sub>FL</sub> /A1
Breaking strength	Thickness <7,5 mm Breaking strength $\geq 700$ N Thickness $\geq 7,5$ mm Breaking strength $\geq 1100$ N
Durability, for: - Internal use - External use: Freeze/thaw resistance	Passed Passed
Resistance to thermal shock	Passed



**Marazzi Group s.r.l. a socio unico,  
Viale Regina Pacis 39  
41049 Sassuolo (MO)**


**05**


**003MRZI**


**EN 14411:2012**


**Dry-pressed ceramic tiles, with water absorption  $3% < E_b \leq 6%$ ,  
for internal walls and floorings**


Reaction to fire	Class A1 <sub>FL</sub> /A1
Breaking strength	Thickness <7,5 mm Breaking strength ≥600 N Thickness ≥7,5 mm Breaking strength ≥1000 N
Durability, for: -Internal use	Passed


	
<p><b>Marazzi Group s.r.l. a socio unico, Viale Regina Pacis 39 41049 Sassuolo (MO)</b></p> <p><b>05</b></p> <p><b>004MRZI</b></p>	
<p><b>EN 14411:2012</b></p> <p><b>Dry-pressed ceramic tiles, with water absorption <math>6% &lt; E_b \leq 10%</math>, for internal walls</b></p>	
Reaction to fire	Class A1
Durability, for: - Internal use	Passed


	
<p><b>Marazzi Group s.r.l. a socio unico, Viale Regina Pacis 39 41049 Sassuolo (MO)</b></p> <p><b>05</b></p> <p><b>005MRZI</b></p>	
<p><b>EN 14411:2012</b></p> <p><b>Dry-pressed ceramic tiles, with water absorption <math>E_b &gt; 10%</math>, for internal walls</b></p>	
Reaction to fire	Class A1
Durability, for: - Internal use	Passed


	
<b>Marazzi Group s.r.l. a socio unico,          Viale Regina Pacis 39          41049 Sassuolo (MO)</b>	
<b>05</b>  <b>006MRZI</b>	
<b>EN 14411:2012</b>  <b>Dry-pressed ceramic tiles, with water absorption <math>3% &lt; E_b \leq 6%</math>,          for internal walls</b>	
Reaction to fire	Class A1
Durability, for: - Internal use	Passed

	
<b>Marazzi Group s.r.l. a socio unico,          Viale Regina Pacis 39          41049 Sassuolo (MO)</b>	
<b>05</b>  <b>007MRZI</b>	
<b>EN 14411:2012</b>  <b>Dry-pressed ceramic tiles, with water absorption <math>E_b &gt; 10%</math>,          for internal walls and floorings</b>	
Reaction to fire	Class A1 <sub>FL</sub> /A1
Breaking strength	Thickness <7,5 mm Breaking strength $\geq 200$ N Thickness $\geq 7,5$ mm Breaking strength $\geq 600$ N
Durability, for: - Internal use	Passed

	
<p><b>Marazzi Group s.r.l. a socio unico, Viale Regina Pacis 39 41049 Sassuolo (MO)</b></p> <p><b>05</b></p> <p><b>008MRZI</b></p>	
<p><b>EN 14411:2012</b></p> <p><b>Extruded ceramic tiles, with water absorption <math>E_b \leq 0,5\%</math>, for internal and external walls and floorings</b></p>	
Reaction to fire	Class A1 <sub>FL</sub> /A1
Breaking strength	Thickness <7,5 mm Breaking strength $\geq 600$ N Thickness $\geq 7,5$ mm Breaking strength $\geq 1300$ N
Durability, for: - Internal use - External use: Freeze/thaw resistance	Passed Passed
Resistance to thermal shock	Passed

	
<p><b>Marazzi Group s.r.l. a socio unico, Viale Regina Pacis 39 41049 Sassuolo (MO)</b></p> <p><b>05</b></p> <p><b>009MRZI</b></p>	
<p><b>EN 14411:2012</b></p> <p><b>Dry-pressed ceramic tiles, with water absorption <math>E_b \leq 0,5\%</math>, for internal and external walls</b></p>	
Reaction to fire	Class A1
Durability, for: - Internal use - External use: Freeze/thaw resistance	Passed Passed
Resistance to thermal shock	Passed

	
<p><b>Marazzi Group s.r.l. a socio unico,</b>  <b>Viale Regina Pacis 39</b>  <b>41049 Sassuolo (MO)</b></p> <p><b>05</b></p> <p><b>010MRZI</b></p>	
<p><b>EN 14411:2012</b></p> <p><b>Dry-pressed ceramic tiles, with water absorption <math>0,5% &lt; E_b \leq 3%</math>,  for internal and external walls</b></p>	
Reaction to fire	Class A1
Durability, for:	
- Internal use	Passed
- External use: Freeze/thaw resistance	Passed
Resistance to thermal shock	Passed

	
<p><b>Marazzi Group s.r.l. a socio unico,</b>  <b>Viale Regina Pacis 39</b>  <b>41049 Sassuolo (MO)</b></p> <p><b>05</b></p> <p><b>011MRZI</b></p>	
<p><b>EN 14411:2012</b></p> <p><b>Dry-pressed ceramic tiles, with water absorption <math>E_b \leq 0,5%</math>,  for internal walls</b></p>	
Reaction to fire	Class A1
Durability, for:	
- Internal use	Passed
Resistance to thermal shock	Passed